

ATTORNEY DOCKET NO.: 6484.0070

United States Patent Application of

Fu-Sheng Chen

for

**ELECTROSTATIC CHUCK SYSTEM AND METHOD FOR
MAINTAINING THE SAME**

LAW OFFICES

FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N. W.
WASHINGTON, DC 20005
202-408-4000

10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1041 1042 1043 1

5

Description of the Related Art

An electrostatic chuck system is used in a semiconductor manufacturing process to hold a semiconductor wafer on a platform during various steps of the manufacturing process by employing an electrostatic force by either placing opposite charges on the wafer and platform or placing charges on either the wafer or platform. An electrostatic chuck system is different from a known mechanical chuck system in that an electrostatic chuck system does not create direct contact with the device side of a semiconductor wafer. A chuck system in general operates either to hold a semiconductor wafer in place during processing or transport the wafer from one equipment to another. The stability of a chuck system promotes uniformity of wafer processing.

20

wafer transferring mechanism (not shown), such as a robotic arm, brings wafer 10 into processing chamber 60 to a position far above platform 12, as shown in Fig. 2a, lift structure 14 moves upward to receive wafer 10. After wafer 10 is received, lift structure 14 lowers and places wafer 10 on platform 12, as shown in Fig. 2b. Second, when processing chamber 60 shown in Fig. 1 completes processing wafer 10, lift structure 14 moves upward to lift wafer 10 away from platform 12 to a position shown in Fig. 2a. The wafer transferring mechanism then enters chamber 60 to receive wafer 10. Lift structure 14 then lowers itself, and thereby places wafer 10 on the transferring mechanism.

Figs. 3a and 3b illustrate two types of lift structures. Referring to Fig. 3a, lift structure 14a includes a disc-shaped lift base 20a having a mounting hole 22a to couple to driving mechanism 16 shown in Fig. 1. Lift structure 14a also includes a plurality of lift pins 24a integrally formed with lift base 20a. Referring to Fig. 3b, a lift structure 14b includes a rectangular-shaped lift base 20b and a plurality of mounting holes 22b to mount lift structure 14b to driving mechanism 16 shown in Fig. 1. Lift structure 14b also includes a plurality of lift pins 24b integrally formed with lift base 20b.

As described above, a traditional lift structure is formed as a single, integral structure with metal or alloy. A lift structure may also be made of steel and has lift pins welded to a lift base. The lift structure, after numerous repeated operations under various harsh temperatures and atmospheric pressures in a processing chamber such as one shown in Fig. 1, often becomes defective due to deformation of one or more of the plurality of lift pins. The entire lift structure will then need to be replaced. Indeed, a lift structure may need to be maintained and replaced on regular intervals before the lift pins are

5 actually deformed to ensure that wafers are not mis-processed. Any maintenance or repair causes a manufacturing equipment to be unavailable during the manufacturing process and therefore adversely impacts on the productivity of the equipment. In addition, any interruption to a semiconductor manufacturing process often decreases the productivity of an entire product line.

However, the repair and maintenance of traditional lift structures involve a complicated procedure. Referring to Fig. 1, electrostatic chuck system 50 also includes a cooling system and control system (not shown) under platform 12. The replacement procedure involves removing the liquid circulating in chuck system 50 and several other components of chuck system 50. The whole process is time-consuming, which means chuck system 50 will be unavailable for production for an extended period of time.

SUMMARY OF THE INVENTION

Accordingly, the present invention is directed to a chuck system that substantially obviates one or more of the problems due to limitations and disadvantages of the related art.

Additional features and advantages of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention. The objectives and other advantages of the invention will be realized and attained by the structures and methods particularly pointed out in the written description and claims thereof, as well as the appended drawings.

To achieve these and other advantages, and in accordance with the purpose of the invention as embodied and broadly described, the present invention provides a chuck system for supporting a semiconductor wafer that includes a chuck platform for supporting the semiconductor wafer, and a lift structure movably coupled with the chuck platform to receive the semiconductor wafer that includes a lift base, and at least one lift pin removably coupled with the lift base, the lift pin having two ends with a first end removably coupled to the lift base and a second end for supporting the semiconductor wafer during lifting operation of the lift structure.

In one aspect of the invention, the first end of the lift pin is threaded and the lift base having a threaded hole for receiving the first end of the lift pin.

In another aspect of the invention, the chuck system further includes a bolt, wherein the first end of the lift pin is threaded and the bolt removably couples the lift pin with the lift base through an opening provided by the lift base.

Also in accordance with the present invention, there is provided a chuck system for supporting a semiconductor wafer that includes a chuck platform for providing support of the semiconductor wafer, and a lift structure movably coupled with the chuck platform for supporting the semiconductor wafer to receive or place the semiconductor wafer on the chuck platform or to lift the wafer away from the chuck platform, the lift structure includes a lift pin, and a lift base for supporting the lift pin, wherein the lift pin has two ends, the lift pin being removably coupled with the lift base, a first end of the lift pin being connected with the lift base, and a second end of the lift pin supporting the semiconductor wafer during lifting or placing operation of the lift structure, and wherein

the lift structure has an external thread on the first end of the lift pin and a matching internal thread in a hole provided by the lift base to removably couple the lift pin and the lift base.

Additionally in accordance with the present invention, there is provided a method of maintaining a lift structure of a chuck system that supports a semiconductor wafer that includes providing a removable first lift pin to a lift base in the lift structure, removing the first lift pin from the lift base with the lift structure being coupled to the chuck system, and mounting a second lift pin to the lift base with the lift structure being coupled to the chuck system.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and, together with the description, serve to explain the objects, advantages, and principles of the invention.

In the drawings:

Fig. 1 illustrates a known electrostatic chuck system;

Fig. 2a illustrates a known electrostatic chuck system in operation;

Fig. 2b illustrates a known electrostatic chuck system in operation;

Fig. 3a illustrates a known lift base that has a mounting hole in its center;

Fig. 3b illustrates a known lift base that has a plurality of mounting holes;

Fig. 4 illustrates a chuck system of the present invention;

Fig. 5 illustrates a lift structure of the present invention;

Fig. 6 illustrates a lift structure of the present invention having a lift pin with an external thread and a bolt for coupling the lift pin to a lift base;

Fig. 7 illustrates a lift base in accordance with the present invention; and

Fig. 8 illustrates how a lift pin may be removed and mounted from a lift base in accordance with the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention provides a chuck system for a semiconductor fabrication process to support a semiconductor wafer and a method of maintaining the chuck system. The present invention generally provides a removable lift pin that can be easily removed and replaced. As a result, the chuck system and method of the present invention minimizes the time required to maintain and replace a chuck system therefore improving productivity of the related equipment and the entire product line.

Fig. 4 illustrates a chuck system in accordance with the present invention.

Referring to Fig. 4, there is provided a chuck system 100 to support a semiconductor wafer 110. Chuck system 100 may be an electrostatic chuck system or other types of chuck systems. Chuck system 100 includes a chuck platform 112 that provides a surface to support wafer 110, and a lift structure 114 movably coupled with chuck platform 112. Lift structure 114 supports wafer 10, preferably from the non-device side, to place wafer

110 on or away from chuck platform 112. As illustrated in Figs. 2a and 2b, lift structure 114 of the present invention operates to primarily serve two purposes. The first purpose is to receive wafer 110 when wafer 110 is brought into a processing chamber 160 and place wafer 110 on platform 112. The second purpose is to lift wafer 110 away from platform 112 after wafer process is completed and remove wafer 110 from processing chamber 160.

Fig. 5 illustrates an embodiment of lift structure 114 in accordance with the present invention. Referring to Fig. 5, lift structure 114 includes a lift base 120 for receiving lift pins 124a, 124b, 124c, and 124d. The number of lift pins used depends on the design of a chuck system and should not be construed to limit the scope of the present invention. As an example, lift pin 124a is removably coupled with lift base 120. One end of lift pin 124a is connected with lift base 120 and the other end of lift pin 124a is used to support wafer 110 during the lifting and placing operations of lift structure 120 to either lift wafer 110 away from platform 112 or place wafer 110 on platform 112 as shown in Fig. 4. Lift pins 124b, 124c, and 124d may be formed similarly as lift pin 124a to be removably coupled with lift base 120.

In one embodiment of the present invention, lift pin 124a has a threaded end and lift base 120 of lift structure 114 includes a hole 126a to receive the threaded end of lift pin 124a. Therefore, as shown in Fig. 5, lift pin 124a can be mounted to or removed from lift base 120 by rotating lift pin 124.

Fig. 6 illustrates another embodiment of the present invention. Referring to Fig. 6, lift structure 114 may additionally include a bolt 130a having a matching internal

thread to removably secure lift pin 124a to lift base 120 through an opening 128a. Bolt 130a may be fixed at the bottom of lift base 120 such that lift pin 124a may be removed or secured to lift base 120 without the need of holding bolt 130a. Lift pin 124a and hole 126a shown in Fig. 5, or bolt 130a shown in Fig. 6 may have more than one set of threads so long as the threads on lift pin 124a and inside hole 126a or bolt 130a are matching.

The lift pins may be made of a variety of materials so long as they provide sufficient support to receive or lift a semiconductor wafer during the placing or lifting operations. Preferably, the present invention has a lift pin made of a conductive material, such as stainless steel or other metals, for the application in an electrostatic chucking system. One purpose of having a conductive lift pin is that a lift structure can help discharging electrostatic charges on a semiconductor wafer when the lift structure is operated to lift the wafer away from the platform. Accordingly, referring to Fig. 4, chuck system 100 may additionally include a grounding device 130 that is conductively coupled to lift structure 114 or lift pin 124a. Grounding device 130 provides a path to discharge electrostatic charges on wafer 110, during wafer-lifting or wafer-placing operation.

Grounding device 130 can conductively couple lift pin 124a to an electrically grounded end when lift structure 114 moves upward to lift wafer 110 away from chuck platform 112, or when lift structure 114 receives wafer 110 when wafer 110 is brought into processing chamber 160. The grounding process helps to remove electrostatic charges on wafer 110 and eliminates unwanted electrostatic charges between wafer 110 and platform 112 during the lifting and placing operations. Referring again to Fig. 5, lift base 120 may be substantially circular and flat, and includes openings 126a, 126b, 126c,

mounted to lift base 120, lift pin 124a can be replaced by lift pin 124e without changing lift base 120.

Chuck system 100 may also include a cooling system and a control system under chuck platform 112. In traditional replacement procedures, liquid circulating in the chuck system 100 will need to be removed together with several other components. These processes usually take time and make processing chamber 160 unavailable for production. The method of the present invention is able to replace lift pin 124a without removing other parts or liquid in chuck system 100. The method, therefore, reduces the cost and time associated with lift-pin replacement operations and increase productivity by improving upon the traditional lift-base design and chuck system maintenance procedure.

It will be apparent to those skilled in the art that various modifications and variations can be made in the disclosed system and method without departing from the scope or spirit of the invention. Other embodiments of the invention will be apparent to those skilled in the art from consideration of the specification and practice of the invention disclosed herein. It is intended that the specification and examples be considered as exemplary only, with a true scope and spirit of the invention being indicated by the following claims.